


CE MARKING - DECLARATION of PERFORMANCE (DoP)

No. DPL009 Fully Reversible Total70 Reinforced Non Escape Route 26/06/2013

| | | |
|---|---|--|
| Fabricator: Dessian Products LTD 9 Apollo Road □□ Adelaide Industrial Estate □□ Belfast Post code: BT12 6HP | Installers details to be added where frames sold unglazed | Installer: Enviro Windows & Cons UK Ltd 1 Rutherford Court □□ 15 North Avenue □□ Clydebank Business Park □□ Clydebank Post code: G81 2QP Or Registered No (5): Certass 0375003A |
| Window or Door | Window | |
| System | Total 70 | |
| Style | Full Reversible (Reinforced) | |
| Application & VACP | Class 3 (Non Escape Route) | |
| Authorised Representative | | |
| Notified Body - hEN(4) | | |
| Notified Body - ETA | | |
| Test/certification body | BSI | KM 13358 |

Essential Characteristics acc. EN 14351-1: 2006 A1:2010

| | | |
|--|---|---|
| Resistance to Windload(3) | Class E2400 (2400 Pa) | |
| Resistance to Water(3) | Class E1050 (1050 Pa) | |
| Dangerous substances(1) | As per declaration by component suppliers | |
| Impact Resistance - doors | NPD | |
| Load bearing of safety devices(1) | NPD | 350N if fitted |
| Height (Doors only) | | |
| Operation forces (Automatic devices only) | NPD | |
| Acoustic Performance | NPD | |
| Thermal transmittance(1) (2) (3) | Minimum requirement (W/m ² K) | Glazing requirement (W/m ² K) Warm Edge Ψ0.04 - Metal Ψ0.06 |
| | 1.6 | 1.4 - 1.3 |
| Radiation Properties | NPD | |
| Air Permeability(3) | Class 4 (600 Pa) | |
| Ability to release (Class 1 escape routes only)(1) | | |
| Company Authorised Personnel - Fabricator | Name: | Dessian Products LTD |
| | Company Position: | Technical Manager |
| | Signature: |  |
| | Date: | 26/06/2013 |
| Company Authorised Personnel - Installer | Name: | Yvonne Girvan |
| | Company Position: | Director |
| | Signature: | |
| | Date: | 26/06/2013 |

Comments/notes:

(1) Threshold values must be entered - No Performance Declared (npd) acceptable for all other Essential Characteristic Values. (2) Thermal transmittance declared value dependant on fitting of specified glazing unit by manufacturer or named installer
(3) Entry performance values declared where improved results may be available for specific applications. (4) Requirement for Notified Body approval of ITT & FPC for Class 1 doors (on escape routes)

Conditions for unglazed frames:

(5) Installers Registered No. - assigned by the fabricator. The fabricator must then hold details, on a register, which the installer signs to agree with the terms and conditions to which the declaration refers. It is the installers responsibility to ensure that the whole window conforms to the declared U value or better by sourcing a suitable glazing unit.